



TAF w/o Inner Ring Series



TAF


Shaft dia. mm.	Identification number	Mass (Ref.)	Boundary dimensions mm					Standard mounting dimension Da	Basic dynamic load rating C	Basic static load rating C0	Allowable rotational speed(2)
		g	Fw	D	C	rs min (1)		Max. mm	N	N	rpm
5	TAF 51010	3.4	5	10	10	0.2		8.4	2 420	1 950	80 000
6	TAF 61210	5.1	6	12	10	0.2		10.4	20550	3 370	70 000
	TAF 61212	6.4	6	12	12	0.2		10.4	3 400	3 170	70 000
7	TAF 71410	6.9	7	14	10	0.2		12.4	3 600	2 960	60 000
	TAF 71412	8.3	7	14	12	0.2		12.4	4 610	4 050	60 000
8	TAF 81512	9.1	8	15	12	0.2		13.4	5 060	4 690	50 000
	TAF 81516	12.9	8	15	16	0.2		13.4	7 080	7 220	50 000
9	TAF 91612	9.8	9	16	12	0.2		14.4	5 490	5 330	45 000
	TAF 91616	13.2	9	16	16	0.2		14.4	7 680	8 210	45 000
10	TAF 101712	10.7	10	17	12	0.2		15.4	5 880	5 970	40 000
	TAF 101716	14.3	10	17	16	0.2		15.4	8 230	9 190	40 000
12	TAF 121912	12.2	12	19	12	0.3		17	6 610	7 260	35 000
	TAF 121916	16.3	12	19	16	0.3		17	9 250	11 200	35 000
14	TAF 142216	21	14	22	16	0.3		20	11 700	13 700	30 000
	TAF 142220	26.5	14	22	20	0.3		20	14 800	18 600	30 000
15	TAF 152316	22.5	15	23	16	0.3		21	12 300	14 900	30 000
	TAF 152320	28	15	23	20	0.3		21	15 600	20 200	30 000
16	TAF 162416	23	16	24	16	0.3		22	12 300	15 100	25 000
	TAF 162420	29	16	24	20	0.3		22	15 500	20 400	25 000
17	TAF 172516	24.5	17	25	16	0.3		23	12 900	16 300	25 000
	TAF 172520	30.5	17	25	20	0.3		23	16 300	22 000	25 000
18	TAF 182616	25.5	18	26	16	0.3		24	13 400	17 500	20 000
	TAF 182620	32	18	26	20	0.3		24	17 000	23 600	20 000
19	TAF 192716	27	19	27	16	0.3		25	14 000	18 700	20 000
	TAF 192720	34	19	27	20	0.3		25	17 700	25 300	20 000
20	TAF 202816	27.5	20	28	16	0.3		26	13 900	18 800	20 000
	TAF 202820	35.5	20	28	20	0.3		26	17 600	25 400	20 000
21	TAF 212916	29	21	29	16	0.3		27	14 400	20 000	19 000
	TAF 212920	36	21	29	20	0.3		27	18 200	27 100	19 000
22	TAF 223016	30	22	30	16	0.3		28	14 900	21 200	18 000
	TAF 223020	37.5	22	30	20	0.3		28	18 900	28 700	18 000
24	TAF 243216	32	24	32	16	0.3		30	15 300	22 500	17 000
	TAF 243220	40.5	24	32	20	0.3		30	19 400	30 500	17 000
25	TAF 253316	33.5	25	33	16	0.3		31	15 800	23 700	16 000
	TAF 253320	42	25	33	20	0.3		31	20 000	32 100	16 000

TAF w/o Inner Ring Series



TAF


TAF w/o Inner Ring Series



TAF


Shaft dia. mm.	Identification number	Mass (Ref.)	Boundary dimensions mm					Standard mounting dimension Da	Basic dynamic load rating C	Basic static load rating C0	Allowable rotational speed(2)
		g	Fw	D	C	rs min (1)		Max. mm	N	N	rpm
26	TAF 263416	34.5	26	34	16	0.3		32	16 300	24 900	15 000
	TAF 263420	43.5	26	34	20	0.3		32	20 600	33 800	15 000
28	TAF 283720	51.5	28	37	20	0.3		35	21 700	37 100	14 000
	TAF 283730	83.5	28	37	30	0.3		35	31 100	58 900	14 000
29	TAF 293820	57	29	38	20	0.3		36	21 600	37 200	14 000
	TAF 293830	85	29	38	30	0.3		36	30 900	59 100	14 000
30	TAF 304020	64.5	30	40	20	0.3		38	25 100	40 100	13 000
	TAF 304030	97.5	30	40	30	0.3		38	36 000	63 900	13 000
32	TAF 324220	68	32	42	20	0.3		40	25 700	42 200	12 000
35	TAF 354520	73.5	35	45	20	0.3		43	26 900	46 200	11 000
	TAF 354530	112	35	45	30	0.3		43	38 600	73 600	11 000
37	TAF 374720	77.5	37	47	20	0.3		45	28 200	50 100	11 000
	TAF 374730	117	37	47	30	0.3		45	40 500	79 800	11 000
38	TAF 384820	79	38	48	20	0.3		46	28 100	50 200	11 000
	TAF 384830	119	38	48	30	0.3		46	40 300	80 000	11 000
40	TAF 405020	83	40	50	20	0.3		48	29 400	54 100	10 000
	TAF 405030	125	40	50	30	0.3		48	42 300	86 200	10 000
42	TAF 425220	86.5	42	52	20	0.3		50	29 900	56 200	9 500
	TAF 425230	130	42	52	30	0.3		50	43 000	89 400	9 500
43	TAF 435330	133	43	53	30	0.3		51	43 800	92 600	9 500
45	TAF 455520	92	45	55	20	0.3		53	31 000	60 200	9 000
	TAF 455530	138	45	55	30	0.3		53	44 600	95 800	9 000
47	TAF 475720	95	47	57	20	0.3		55	31 500	62 200	8 500
	TAF 475730	144	47	57	30	0.3		55	45 200	99 100	8 500
50	TAF 506225	159	50	62	25	0.3		60	43 000	85 300	8 000
	TAF 506235	225	50	62	35	0.3		60	58 000	125 000	8 000
55	TAF 556825	193	55	68	25	0.3		66	45 400	94 000	7 500
	TAF 556835	255	55	68	35	0.3		66	61 200	138 000	7 500
60	TAF 607225	187	60	72	25	0.3		70	47 500	103 000	6 500
	TAF 607235	260	60	72	35	0.3		70	64 100	151 000	6 500
65	TAF 657825	225	65	78	25	0.6		74	49 600	112 000	6 000
	TAF 657835	315	65	78	35	0.6		74	67 000	164 000	6 000

TAF w/o Inner Ring Series



TAF


TAF w/o Inner Ring Series



TAF

Shaft dia. mm.	Identification number	Mass (Ref.)	Boundary dimensions mm					Standard mounting dimension Da	Basic dynamic load rating C	Basic static load rating C0	Allowable rotational speed(2)
		g	Fw	D	C	rs min (1)		Max. mm	N	N	rpm
68	TAF 688225	250	68	82	25	0.6		78	54 800	117 000	6 000
	TAF 688235	350	68	82	35	0.6		78	72 000	166 000	6 000
70	TAF 708535	395	70	85	35	0.6		81	73 000	171 000	5 500
73	TAF 739025	335	73	90	25	1		85	61 100	127 000	5 500
	TAF 739035	475	73	90	35	1		85	80 400	181 000	5 500
75	TAF 759225	345	75	92	25	1		87	62 100	131 000	5 500
	TAF 759235	485	75	92	35	1		87	81 700	186 000	5 500
80	TAF 809525	315	80	95	25	1		90	59 400	137 000	5 000
	TAF 809535	445	80	95	35	1		90	78 100	195 000	5 000
85	TAF 8510525	435	85	105	25	1		100	76 300	145 000	4 500
	TAF 8510535	610	85	105	35	1		100	102 000	210 000	4 500
90	TAF 9011025	455	90	110	25	1		105	77 300	150 000	4 500
	TAF 9011035	640	90	110	35	1		105	103 000	217 000	4 500
95	TAF 9511526	495	95	115	26	1		110	79 700	159 000	4 000
	TAF 9511536	690	95	115	36	1		110	106 000	231 000	4 000
100	TAF 10012026	525	100	120	26	1		115	82 400	168 000	4 000
	TAF 10012036	725	100	120	36	1		115	110 000	244 000	4 000
110	TAF 11013030	660	110	130	30	1		125	106 000	240 000	3 500
	TAF 11013040	880	110	130	40	1		125	134 000	324 000	3 500

TAF w/o Inner Ring Series



TAF